

MP 450 FW Ultra



EasyPlug



D

Pan capacity

up to 100 litres

A

SALES DESCRIPTION

Intended for Institutional and commercial caterers. Intensive use.  
Whisk attachment for processing mashed potatoes, pan cakes, whipped cream...

B

TECHNICAL DESCRIPTION

MP 450 FW Ultra Immersion Blender. Single phase. Power 500 Watts ; Variable speed from 250 to 1500 rpm. Metal gear box even more resistant to support heavy strenghts. "EasyPlug" system featuring detachable power cord.

C

TECHNICAL DATA

<b>Output power</b>	500 W	
<b>Electrical datas</b>	Single phase - Plug supplied	
<b>Variable speed</b>	250 - 1,500 rpm	
<b>Recyclability</b>	95%	
<b>Net weight</b>	6.1 kg	
	<b>Supply</b>	<b>Amperage</b>
	220-240/50-60/1	2.3 Amp
	240V/50/1 UK plug	2.3 Amp
	120V/60/1	4.5 Amp
	220V/60/1 SAU*	2.3 Amp
		<b>Reference</b>
		34880L
		34881L
		34885L
		34888L

\*For commercial use only

STANDARDS

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34



E

CHARACTERISTICS AND BENEFITS

MOTOR UNIT

- Power 500 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Lug on motor housing serves as a rest and pivot on the pan rim for greater user comfort
- Variable speed: 250 - 1,500 rpm
- Self-regulating speed system
- New patented "EasyPlug" system making it easier to replace the power cord during after-sales servicing
- Cord winding system for tidy storage and optimum lifespan

WHISK

- Whisk attachment equipped with metal gear box even more resistant when processing pan cakes or fresh mashed potatoes.
- Fast coupling of the whisks on the gear box and the gear box on the motor base for easy assembling and dismantling.

STANDARD ATTACHMENTS

- Wall-mounted immersion blender holder
- Tool for fixing and detaching the blades

MP 450 FW Ultra

MP 450 FW Ultra



DRAWINGS & DIMENSIONS

Power cord and plug supplied

