

MP 450 XL FW Ultra



D

Pan capacity

up to 100 litres

**A SALES DESCRIPTION**

Intended for institutional and commercial caterers. Intensive use. Mixing Tool for potato flakes, dry soups, deshydrated base for sauce, spices + sauces, deshydrated mixes for pastry.

**B TECHNICAL DESCRIPTION**

MP 450 XL FW Ultra Immersion Blender. Single phase. Power 500 Watts ; Variable speed from 250 to 1500 rpm. Metal gear box resistant to support heavy strenghts. "EasyPlug" system featuring detachable power cord.

**C TECHNICAL DATA**

<b>Output power</b>	500 W	
<b>Electrical datas</b>	Single phase - Plug supplied	
<b>Variable speed</b>	150 - 510 rpm	
<b>Recyclability</b>	95%	
<b>Net weight</b>	5.3 Kg	
	<b>Supply</b>	<b>Amperage</b>
	220-240/50-60/1	2.3 Amp
	240V/50/1 UK plug	2.3 Amp
		<b>Reference</b>
		34280L
		34281L

**E CHARACTERISTICS AND BENEFITS**

**MOTOR UNIT**

- Power 500 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Lug on motor housing serves as a rest and pivot on the pan rim for greater user comfort
- Variable speed: 150 - 510 rpm
- Self-regulating speed system
- New patented "EasyPlug" system making it easier to replace the power cord during after-sales servicing
- Cord winding system for tidy storage and optimum lifespan

**MIXING TOOL ATTACHMENT**

- A metal whisk box to stand up to heavy duty use

**STANDARD ATTACHMENTS**

- Wall-mounted immersion blender holder

**STANDARDS**

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34



MP 450 XL FW Ultra

MP 450 XL FW Ultra

G

DRAWINGS & DIMENSIONS

Power cord and plug supplied

